

**PGS
LOW COST PRESSURE GAUGE**



Flow
Pressure
Level
Temperature
measurement
monitoring
control

P1



- **Brass/Bronze Wetted Parts**
- **ABS Housing**
- **Polycarbonate Window**
- **2-1/2" Dial**
- **3-2-3% Accuracy**



USA

KOBOLD Instruments Inc.
1801 Parkway View Drive
USA-Pittsburgh, PA 15205
☎ +1 412-788-2830
Fax +1 412-788-4890
E-mail: info@koboldusa.com



CANADA

KOBOLD Instruments Canada Inc.
9A Aviation
Pointe-Claire, QC H9R 4Z2
☎ +1 514-428-8090
Fax +1 514-428-8899
E-mail: kobold@kobold.ca

Visit KOBOLD Online at
www.kobold.com

Model:
PGS



Features

- Brass/Bronze Wetted Parts
- ABS Housing
- Polycarbonate Window
- 2-1/2" Dial
- 3 - 2 - 3% Accuracy

KOBOLD PGS pressure gauges are ideal for rugged applications and harsh environments. The PGS features an ABS housing and a full view polycarbonate window. The PGS movement design offers superior shock, vibration and pulsation resistance.



KOBOLD PGS Pressure Gauge

Specifications

- Ranges:** 0-200 PSIG
- Maximum Operating Pressure:** 75% of full scale
- Sensing Element:** Bourdon tube
- Dial size:** 2 1/2"
- Accuracy:** 3-2-3% Grade B
- Operating Temperature:**
Medium: -40 to 150°F Max
- Fitting:** 1/4" NPT

Materials of Construction

- Wetted Parts**
Tube: Bronze
Fitting: Brass
- Exterior**
Movement: Brass/Polyester
Housing: ABS (Acrylonitrile Butadiene Styrene)
Dial: Black figures on white painted steel
Pointer: Black painted aluminum
Window: Polycarbonate snap-in

PGS Ordering Data

Range (PSIG)	Model Number
0-30	PGS-1030
0-60	PGS-1060
0-100	PGS-1100
0-200	PGS-1200