



SPECIFICATIONS														
MODEL NO.	Capacity *				Dimensions *** In.							Weight**** (lbs)		
	Pounds / hr	Boiler HP	Reserve Capacity (gal)	Tank Volume (gal)	A Tank Length	B Tank Dia.	C Overall Width	D Height	E** Water Inlet	F** Steam Inlet	Dry	Operating	Overfull	
DAT3048	3,500	100	92	184	69	30	40	132	3/4	3/4	1,875	2,650	3,530	
DAT3072	6,300	185	128	256	93	30	40	132	1	1	2,000	3,065	4,350	
DAT3660	8,100	235	162	327	96	36	46	138	1	1	2,300	3,650	5,200	
DAT3696	12,000	350	241	483	123	36	48	138	1 1/2	1 1/2	2,700	4,707	6,930	
DAT36132	16,000	466	322	639	160	36	48	138	1 1/2	1 1/2	3,120	5,800	8,650	
DAT42120	20,500	594	410	820	154	42	56	144	2	2	3,750	7,200	10,825	
DAT48108	25,020	725	501	990	142	48	62	148	2	2	4,000	8,180	12,380	
DAT5496	30,000	870	600	1150	133	54	68	154	2	2	5,200	10,200	15,200	
DAT54120	35,000	1,015	700	1380	154	54	68	154	2 1/2	2 1/2	6,150	11,985	18,200	

* - Capacity based on at least 10 minutes storage capacity.
 ** - Depends on pressure.
 *** - Standard frame height. Height dimensions may vary upon pump specification and job condition.
 **** - Weights vary based on pump selection job conditions.

RECOMMENDED CLEARANCES	PANEL 36-48"	TOP 18"	SIDE 24"	BACK 6-24"	MANHOLE SIDE 24"
------------------------	-----------------	------------	-------------	---------------	---------------------

Notes: Dimensions are for reference only. Due to continuous improvement, specifications are subject to change without notice.